

# Fiberglass Pipe Wrapping Tissue

## PRODUCT DESCRIPTION

Fiberglass pipe wrapping tissue is used for pipeline coating corrosion protection after combining with asphalt, coal tar, etc., with excellent impermeability and resistance to harsh environment.

Pipe wrapping tissue is widely used in oil, natural gas and other underground transportation pipeline coating for anti-corrosion.



## CHARACTERISTICS

- ◆ Fiber Dispersed Uniformly
- ◆ High Strength, Good Flexibility
- ◆ Easy to Immerse into Bitumen and Coal-tar
- ◆ Good Anti-permeability and resistance to
- ◆ Environmental Media

## TECHNICAL DATA

| Product code        | Unit Weight      | LOI      | Tensile Strength MD | Tensile Strength CD | Moisture Content |
|---------------------|------------------|----------|---------------------|---------------------|------------------|
|                     | g/m <sup>2</sup> | %        | N/5CM               | N/5CM               | %                |
| PW50-T15            | 50               | ≤20      | ≥ 220               | ≥70                 | ≤ 1.0            |
| Testing Basis       | ISO3374          | ISO 1887 | ISO3342             | ISO 3344            |                  |
| Paper core diameter | 76/152mm         |          |                     |                     |                  |

Remark: 1. Common roll width: 23cm, 1m, 1.02m, other size can be customized according to customer' s demand.  
2. The technical data above is for reference only

## PACKING

Everyroll in plastic film.

## STORAGE

This product should be stored in a dry, ventilated and rainproof place, with temperatures from 5°Cto 35°C and humidity between 35% and 65%. It is recommended to be kept in intact package when not used to avoid damp.

Version #: No.201911

Address: No.20 Jiangjun Ave., Nanjing, P.R. China

Tel.: 0086 25 52270147 / 58321911

URL: [www.fiberglassnonwoven.com](http://www.fiberglassnonwoven.com)

Fax: 0086 25 58321442

E-mail: [sales@njefg.com](mailto:sales@njefg.com)

WhatsApp: 0086 18851651909